ADOPTED: MARCH 22, 2005

GENERAL

1. The applicant agrees to defend, indemnify and hold harmless the City of La Quinta ("City"), its agents, officers and employees from any claim, action or proceeding to attack, set aside, void, or annul the approval of this Site Development Permit, or any Final Map recorded thereunder. The City shall have sole discretion in selecting its defense counsel.

The City shall promptly notify the applicant of any claim, action or proceeding and shall cooperate fully in the defense.

- 2. Prior to the issuance of any grading, construction, or building permit by the City, the applicant shall obtain any necessary clearances and/or permits from the following agencies:
 - Fire Marshal
 - Public Works Department (Grading Permit, Improvement Permit)
 - Community Development Department
 - Riverside Co. Environmental Health Department
 - Desert Sands Unified School District
 - Coachella Valley Water District (CVWD)
 - Imperial Irrigation District (IID)
 - California Water Quality Control Board (CWQCB)
 - SunLine Transit Agency
 - SCAQMD Coachella Valley

The applicant is responsible for all requirements of the permits and/or clearances from the above listed agencies. When the requirements include approval of improvement plans, the applicant shall furnish proof of such approvals when submitting those improvements plans for City approval.

A project-specific NPDES construction permit must be obtained by the applicant; and who then shall submit a copy of the Regional Water Quality Control Board's ("RWQCB") acknowledgment of the applicant's Notice of Intent ("NOI"), prior to the issuance of a grading or site construction permit by the City.

ADOPTED: MARCH 22, 2005

- 3. The applicant shall comply with applicable provisions of the City's NPDES stormwater discharge permit, Sections 8.70.010 et seq. (Stormwater Management and Discharge Controls), and 13.24.170 (Clean Air/Clean Water), LQMC; Riverside County Ordinance No. 457; and the State Water Resources Control Board's Order No. 99-08-DWQ.
 - A. For construction activities including clearing, grading or excavation of land that disturbs one (1) acre or more of land, or that disturbs less than one (1) acre of land, but which is a part of a construction project that encompasses more than one (1) acre of land, the Permitee shall be required to submit a Storm Water Pollution Protection Plan ("SWPPP").

The applicant or design professional can obtain the California Stormwater Quality Association SWPPP template at www.cabmphandbooks.com for use in their SWPPP preparation.

- B. The applicant's SWPPP shall be approved by the City Engineer prior to any on or off-site grading being done in relation to this project.
- C. The applicant shall ensure that the required SWPPP is available for inspection at the project site at all times through and including acceptance of all improvements by the City.
- D. The applicant's SWPPP shall include provisions for all of the following Best Management Practices ("BMPs") (8.70.020 (Definitions), LQMC):
 - 1) Temporary Soil Stabilization (erosion control).
 - 2) Temporary Sediment Control.
 - Wind Erosion Control.
 - 4) Tracking Control.
 - 5) Non-Storm Water Management.
 - 6) Waste Management and Materials Pollution Control.

ADOPTED: MARCH 22, 2005

- E. All erosion and sediment control BMPs proposed by the applicant shall be approved by the City Engineer prior to any onsite or offsite grading, pursuant to this project.
- F. The approved SWPPP and BMPs shall remain in effect for the entire duration of project construction until all improvements are completed and accepted by the City.
- 5. Permits issued under this approval shall be subject to the provisions of the Infrastructure Fee Program and Development Impact Fee program in effect at the time of issuance of building permit(s).

PROPERTY RIGHTS

- 6. Prior to issuance of any permit(s), the applicant shall acquire or confer easements and other property rights necessary for the construction or proper functioning of the proposed development. Conferred rights shall include irrevocable offers to dedicate or grant access easements to the City for emergency services and for maintenance, construction and reconstruction of essential improvements.
- 7. The applicant shall offer for dedication of all public street right-of-ways in conformance with the City's General Plan, Municipal Code, applicable specific plans, and/or as required by the City Engineer.
- 8. The public street right-of-way offers for dedication required for this development include:

A. PUBLIC STREETS

- 1) Dune Palms Road (Primary Arterial, Option A, 110' ROW) The standard 55 from the centerline of Dune Palms Road for a total 110-foot ultimate developed right of way except for:
 - A) An additional right of way dedication for a deceleration lane at the Gas Station driveway of sixty three (63') feet from the centerline and length to be determined by a traffic study prepared for the applicant by a licensed traffic engineer per

ADOPTED: MARCH 22, 2005

Engineering Bulletin # 03-08 however at a minimum 100 feet long plus a variable dedication of an additional 50 feet to accommodate improvements conditioned under <u>STREET AND TRAFFIC IMPROVEMENTS</u>, and

- B) An additional right of way dedication for a deceleration lane at the Primary Entry intersection of sixty three (63') feet from the centerline and extending to the Gas Station driveway to accommodate improvements conditioned under STREET AND TRAFFIC IMPROVEMENTS.
- Dedications shall include additional widths as necessary for dedicated right and left turn lanes, bus turnouts, and other features contained in the approved construction plans.

Pursuant to this requirement, the Applicant shall include in the submittal packet submitted for off-site street improvement plan checking, an offsite street geometric layout, drawn at 1" equals 40 feet, detailing the following design aspects: median curb line, outside curb line, lane line alignment including lane widths, left turn lanes, deceleration lane(s) and bus stop turnout(s). The geometric layout shall be accompanied with sufficient professional engineering studies to confirm the appropriate length of all proposed turn pockets and auxiliary lanes that may impact the right of way dedication required of the project and the associated landscape setback requirement.

- 10. When the City Engineer determines that access rights to the proposed street right-of-ways shown on the approved Site Development Permit are necessary, the applicant shall grant the necessary right-of-ways within 60 days of a written request by the City.
- 11. The applicant shall create perimeter landscaping setbacks along all public right-ofways as follows:
 - A. Dune Palms Road (Primary Arterial) 20-foot from the R/W-P/L.

The setback requirements shall apply to all frontages including, but not limited to, remainder parcels and sites dedicated for utility purposes.

ADOPTED: MARCH 22, 2005

Where public facilities (e.g., sidewalks) are placed on privately-owned setbacks, the applicant shall offer for dedication blanket easements for those purposes on the Final Map.

- 12. Direct vehicular access to Dune Palms Road from parcels with frontage along Dune Palms Road is restricted, except for those access points identified on the Site Development Permit site plan, or as otherwise conditioned in these conditions of approval.
- 13. The applicant shall re-design the alignment of driveway #8 (located approximately 1130 feet south of Highway 111) so its centerline projects across the street to a location that is 35 feet south of the joint property line separating parcels 3 and 4 of Parcel Map 28422.
- 14. Ancillary vehicular access to Highway 111 shall be through the signalized intersection at La Quinta Drive and existing access driveways for Parcel Map No. 30420. Reciprocal access easements to the adjacent properties shall be acquired by the developer and submitted to the Community Development Department.
- 15. The applicant shall furnish proof of easements, or written permission, as appropriate, from those owners of all abutting properties on which grading, retaining wall construction, permanent slopes, or other encroachments will occur.
- 16. The applicant shall cause no easement to be granted, or recorded, over any portion of the subject property between the date of approval of the Site Development Permit and the date of recording of any Final Map, unless such easement is approved by the City Engineer.

IMPROVEMENT PLANS

As used throughout these Conditions of Approval, professional titles such as "engineer," "surveyor," and "architect," refers to persons currently certified or licensed to practice their respective professions in the State of California.

17. Improvement plans shall be prepared by or under the direct supervision of qualified engineers and/or architects, as appropriate, and shall comply with the provisions of Section 13.24.040 (Improvement Plans), LQMC.

18. The following improvement plans shall be prepared and submitted for review and approval by the Public Works Department. A separate set of plans for each line item specified below shall be prepared. The plans shall utilize the minimum scale specified, unless otherwise authorized by the City Engineer in writing. Plans may be prepared at a larger scale if additional detail or plan clarity is desired. Note, the applicant may be required to prepare other improvement plans not listed here pursuant to improvements required by other agencies and utility purveyors.

A. On-Site Rough Grading Plan 1" = 40' Horizontal

B. PM10 Plan 1'' = 40' Horizontal

C. SWPPP 1'' = 40' Horizontal

NOTE: A through C to be submitted concurrently.

D. Off-Site Street Improvement/Storm Drain Plan

1" = 40' Horizontal, 1" = 4' Vertical

E. Off-Site Signing & Striping Plan 1" = 40' Horizontal The Off-Site street improvement plans shall have separate plan sheet(s) (drawn at 20 scale) that show the meandering sidewalk, mounding, and berming design in the combined parkway and landscape setback area.

F. Traffic Signal Modification Plan 1'' = 20' Horizontal

G. Off-Site Median Landscaping Plans 1" = 40' Horizontal

NOTE: D through F to be submitted concurrently. Caltrans approval required for all work within Highway 111 right of way.

H. Precise Grading Non-Residential Plan 1" = 30' Horizontal

Other engineered improvement plans prepared for City approval that are not listed above shall be prepared in formats approved by the City Engineer prior to commencing plan preparation.

ADOPTED: MARCH 22, 2005

All Off-Site Plan & Profile Street Plans and Signing & Striping Plans shall show all existing improvements for a distance of at least 200-feet beyond the project limits, or a distance sufficient to show any required design transitions.

All On-Site Signing & Striping Plans shall show, at a minimum; Stop Signs, Limit Lines and Legends, No Parking Signs, Raised Pavement Markers (including Blue RPMs at fire hydrants) and Street Name Signs per Public Works Standard Plans and/or as approved by the Engineering Department.

"Rough Grading" plans shall normally include perimeter walls with <u>Top Of Wall & Top Of Footing elevations</u> shown. All footings shall have a minimum of 1-foot of cover, or sufficient cover to clear any adjacent obstructions.

The applicant shall prepare an accessibility assessment on a marked up print of the building floor plan identifying every building egress and notes the 2001 California Building Code accessibility requirements associated with each door. The assessment must comply with submittal requirements of the Building & Safety Department. A copy of the reviewed assessment shall be submitted to the Engineering Department in conjunction with the Site Development Plan when it is submitted for plan checking.

"Precise Grading Non-Residential" plans shall normally include all on-site surface improvements including but not necessarily limited to finish grades for curbs & gutters, building floor elevations, parking lot improvements and ADA requirements.

- 19. The City maintains standard plans, detail sheets and/or construction notes for elements of construction which can be accessed via the Online Engineering Library at the City website (www.la-quinta.org). Navigate to the Public Works Department home page and look for the Online Engineering Library hyperlink.
- 20. The applicant shall furnish a complete set of the AutoCAD files of all approved improvement plans on a storage media acceptable to the City Engineer. The files shall be saved in a standard AutoCAD format so they may be fully retrievable through a basic AutoCAD program.

At the completion of construction, and prior to the final acceptance of the improvements by the City, the applicant shall update the AutoCAD files in order to reflect the as-built conditions.

ADOPTED: MARCH 22, 2005

Where the improvement plans were not produced in a standard AutoCAD format, or a file format that can be converted to an AutoCAD format, the City Engineer will accept raster-image files of the plans.

IMPROVEMENT SECURITY AGREEMENTS

- 21. Upon approval of this Site Development Permit, the applicant shall initiate the parcel map process to establish the parcels. The following conditions will be applicable to finalizing the final parcel map.
- 22. Improvements to be made, or agreed to be made, shall include the removal of any existing structures or other obstructions which are not a part of the proposed improvements; and shall provide for the setting of the final survey monumentation.

When improvements are phased through a "Phasing Plan," or an administrative approval (e.g., Site Development Permits), all off-site improvements and common onsite improvements (e.g., backbone utilities, retention basins, perimeter walls, landscaping and gates) shall be constructed, or secured through a SIA, prior to the issuance of any permits in the first phase of the development, or as otherwise approved by the City Engineer.

Improvements and obligations required of each subsequent phase shall either be completed, or secured through a SIA, prior to the occupancy of permanent buildings within such latter phase, or as otherwise approved by the City Engineer.

In the event the applicant fails to construct the improvements for the development, or fails to satisfy its obligations for the development in a timely manner, pursuant to the approved phasing plan, the City shall have the right to halt issuance of all permits, and/or final inspections, withhold other approvals related to the development of the project, or call upon the surety to complete the improvements.

- 23. Depending on the timing of the development of the Site Development Permit improvements, and the status of the off-site improvements at the time, the applicant may be required to:
 - A. Construct off-site street transition improvements;
 - B. Secure the costs for future improvements that are to be made by others; and

ADOPTED: MARCH 22, 2005

C. To agree to any combination of these means, as the City may require.

Off-Site Improvements should be completed on a first priority basis. The applicant shall complete Off-Site Improvements in the first phase of construction.

In the event that any of the improvements required for this development are constructed by the City, the applicant shall, prior to the approval of the Final Map, or the issuance of any permit related thereto, reimburse the City for the costs of such improvements.

24. If the applicant elects to utilize the secured agreement alternative, the applicant shall submit detailed construction cost estimates for all proposed on-site and off-site improvements, including an estimate for the final survey monumentation, for checking and approval by the City Engineer. Such estimates shall conform to the unit cost schedule adopted by City resolution, or ordinance.

For items not listed in the City's unit cost schedule, the proposed unit costs shall be approved by the City Engineer.

At the time the applicant submits its detailed construction cost estimates for conditional approval of the Final Map by the City Council, the applicant shall also submit one copy each of an 8-1/2" x 11" reduction of each page of the Final Map, along with a copy of an 8-1/2" x 11" Vicinity Map.

Estimates for improvements under the jurisdiction of other agencies shall be approved by those agencies and submitted to the City along with the applicant's detailed cost estimates.

- 25. Security will not be required for telephone, natural gas, or Cable T.V. improvements.
- 26. Should the applicant fail to construct the improvements for the development, or fail to satisfy its obligations for the development in a timely manner, the City shall have the right to halt issuance of building permits, and/or final building inspections, withhold other approvals related to the development of the project, or call upon the surety to complete the improvements.

GRADING

- 27. The applicant shall comply with the provisions of Section 13.24.050 (Grading Improvements), LQMC.
- 28. Prior to occupancy of the project site for any construction, or other purposes, the applicant shall obtain a grading permit approved by the City Engineer.
- 29. To obtain an approved grading permit, the applicant shall submit and obtain approval of all of the following:
 - A. A grading plan prepared by a qualified engineer,
 - B. A preliminary geotechnical ("soils") report prepared by a qualified engineer,
 - C. A Fugitive Dust Control Plan prepared in accordance with Chapter 6.16, (Fugitive Dust Control), LQMC, and
 - D. A Best Management Practices report prepared in accordance with Sections 8.70.010 and 13.24.170 (NPDES stormwater discharge permit and Storm Management and Discharge Controls), LQMC.

All grading shall conform to the recommendations contained in the Preliminary Soils Report, and shall be certified as being adequate by a soils engineer, or by an engineering geologist.

A statement shall appear on the Grading Plan(s) that a soils report has been prepared in accordance with the California Health & Safety Code § 17953.

The applicant shall furnish security, in a form acceptable to the City, and in an amount sufficient to guarantee compliance with the approved Fugitive Dust Control Plan provisions as submitted with its application for a grading permit.

30. The applicant shall maintain all open graded, undeveloped land in order to prevent wind and/or water erosion of such land. All open graded, undeveloped land shall either be planted with interim landscaping, or stabilized with such other erosion control measures, as were approved in the Fugitive Dust Control Plan.

ADOPTED: MARCH 22, 2005

- 31. Grading within the perimeter setback and parkway areas shall have undulating terrain and shall conform with the requirements of LQMC Section 9.60.240(F) except as otherwise modified by this condition requirement. The maximum slope shall not exceed 3:1 anywhere in the landscape setback area, except for the backslope (i.e. the slope at the back of the landscape lot) which shall not exceed 2:1 if fully planted with ground cover. The maximum slope in the first six (6) feet adjacent to the curb shall not exceed 4:1 when the nearest edge of sidewalk is within six feet (6') of the curb, otherwise the maximum slope within the right of way shall not exceed 3:1. All unpaved parkway areas adjacent to the curb shall be depressed one and one-half inches (1.5") in the first eighteen inches (18") behind the curb.
- 32. The applicant shall abandoned any existing wells within the Site Development Permit boundaries as approved by CVWD and the City Engineer.
- 33. Building pad elevations on the rough grading plan submitted for City Engineer's approval shall conform with pad elevations shown on the site development permit site plan, unless the pad elevations have other requirements imposed elsewhere in these Conditions of Approval.
- 34. Prior to any site grading or regrading that will raise or lower any portion of the site by more than plus or minus three tenths of a foot from the elevations shown on the approved Site Development Permit, the applicant shall submit the proposed grading changes to the City Staff for a substantial conformance finding review.
- 35. Prior to the issuance of a building permit for any building lot, the applicant shall provide a lot pad certification stamped and signed by a qualified engineer or surveyor.

Each pad certification shall list the pad elevation as shown on the approved grading plan, the actual pad elevation and the difference between the two, if any. Such pad certification shall also list the relative compaction of the pad soil. The data shall be organized by lot number, and listed cumulatively if submitted at different times.

<u>DRAINAGE</u>

36. Stormwater falling on site during the 100 year storm shall be retained within the development, unless otherwise approved by the City Engineer. The tributary drainage area shall extend to the centerline of adjacent public streets. The design storm shall be either the 3 hour, 6 hour or 24 hour event producing the greatest total run off.

ADOPTED: MARCH 22, 2005

The applicant shall design to contain all stormwater in reinforced concrete underground retention storage within the parking area or other alternative design as approved by the City Engineer. Additionally, the applicant's design professional shall design the underground retention storage and the Gas Station per Riverside Flood Control and Water Conservation District guidelines and incorporate necessary BMPs in each design to ensure that gasoline leakage and spillages do not become entrapped in the underground retention storage.

37. If above ground retention is proposed, the applicant shall design for the retention basins to comply with the provisions of Section 13.24.120 (Drainage), LQMC, Engineering Bulletin No. 97.03. More specifically, stormwater falling on site during the 100 year storm shall be retained within the development, unless otherwise approved by the City Engineer. Additionally, the 100 year stormwater shall be retained within the interior street right of way. The tributary drainage area shall extend to the centerline of adjacent public streets and include any resulting uncaptured tributary stormwater flows. The design storm shall be either the 3 hour, 6 hour or 24 hour event producing the greatest total run off.

In design of retention basins, the maximum percolation rate shall be two inches per hour. The percolation rate will be considered to be zero unless the applicant provides site specific data indicating otherwise.

Nuisance water shall be retained on site and shall be disposed of in a trickling sand filter and leach field or equivalent system approved by the City Engineer. The sand filter and leach field shall be designed to contain surges of up to 3 gph/1,000 sq. ft. of landscape area, and infiltrate 5 gpd/1,000 sq. ft. The sand filter and leach field shall be designed to contain nuisance water surges from landscape area, residential unit, and off-site street nuisance water. Flow from adjacent well sites shall be designed for retention area percolation by separate infiltration system approved by the City Engineer. The sand filter design shall be per La Quinta Standard 370 with the equivalent of 137.2 gph of water feed per sand filter to accept the abovementioned nuisance water requirements. Leach line requirements are 1.108 feet of leach line per gph of flow.

38. Stormwater may not be retained in landscaped parkways or landscaped setback lots Only incidental storm water (precipitation which directly falls onto the setback) will be permitted to be retained in the landscape setback areas. The perimeter setback and parkway areas in the street right-of-way shall be shaped with berms and mounds, pursuant to Section 9.100.040(B)(7), LQMC.

ADOPTED: MARCH 22, 2005

- 39. The design of the development shall not cause any increase in flood boundaries, levels or frequencies in any area outside the development.
- 40. The development shall be graded to permit storm flow in excess of retention capacity to flow out of the development through a designated overflow and into the historic drainage relief route.
- 41. Storm drainage historically received from adjoining property shall be received and retained or passed through into the historic downstream drainage relief route.

UTILITIES

- 42. The applicant shall comply with the provisions of Section 13.24.110 (Utilities), LQMC.
- 43. The applicant shall obtain the approval of the City Engineer for the location of all utility lines within any right-of-way, and all above-ground utility structures including, but not limited to, traffic signal cabinets, electric vaults, water valves, and telephone stands, to ensure optimum placement for practical and aesthetic purposes.
- 44. Existing overhead utility lines within, or adjacent to the proposed development, and all proposed utilities shall be installed underground.
 - All existing utility lines attached to joint use 92 KV transmission power poles are exempt from the requirement to be placed underground.
- 45. Underground utilities shall be installed prior to overlying hardscape. For installation of utilities in existing improved streets, the applicant shall comply with trench restoration requirements maintained, or required by the City Engineer.

The applicant shall provide certified reports of all utility trench compaction for approval by the City Engineer.

STREET AND TRAFFIC IMPROVEMENTS

46. The applicant shall comply with the provisions of Sections 13.24.060 (Street Improvements), 13.24.070 (Street Design - Generally) & 13.24.100 (Access For Individual Properties And Development), LQMC for public streets; and Section 13.24.080 (Street Design - Private Streets), where private streets are proposed.

ADOPTED: MARCH 22, 2005

47. The applicant shall construct the following street improvements to conform with the General Plan (street type noted in parentheses.)

A. OFF-SITE STREETS

1) Dune Palms Road (Primary Arterial; 110' R/W option):

Widen the west side of the street along all frontage adjacent to the Site Development Permit boundary to its ultimate width on the west side as specified in the General Plan and the requirements of these conditions. Rehabilitate and/or reconstruct existing roadway pavement as necessary to augment and convert it from a rural county-road design standard to La Quinta's urban arterial design standard. The west curb face shall be located forty three feet (43') west of the centerline, except at locations where additional street width is needed to accommodate:

- a) A deceleration/right turn only lane on Dune Palm Road at the Primary Entry. The west curb face shall be located fifty one feet (51') west of the centerline and extending to the Gas Station Driveway.
- b) A deceleration/right turn only lane on Dune Palm Road at the Gas Station Driveway. The west curb face shall be located fifty one feet (51') west of the centerline and length to be determined by a traffic study prepared for the applicant by a licensed traffic engineer per Engineering Bulletin # 03-08. As a minimum, the required length shall be 100 feet plus a variable dedication of an additional 50 feet.

Other required improvements in the Dune Palms Road right or way and/or adjacent landscape setback area include:

- c) All appurtenant components such as, but not limited to: curb, gutter, traffic control striping, legends, and signs.
- d) 8-foot wide meandering sidewalk. The meandering sidewalk shall have an arrhythmic horizontal layout that utilizes concave and convex curves with respect to the curb line that either touches

ADOPTED: MARCH 22, 2005

the back of curb or approaches within five feet of the curb at intervals not to exceed 250 feet. The sidewalk curvature radii should vary between 50 and 300 feet and at each point of reverse curvature, the radius should change to assist in creating the arrhythmic layout. The sidewalk shall meander into the landscape setback lot and approach within 5 feet of the perimeter wall at intervals not to exceed 250 feet.

e) An 18 - foot wide raised landscaped median along the entire boundary of the Specific Plan plus variable width as needed to accommodate a dual left turn for the north bound Dune Palms Road traffic turning left to westbound Highway 111. The length shall be 250 feet with a 100-foot (50 to 1) taper.

Additional median openings are required for the following:

Left turn movements into the Proposed Gas Station Entry (approximately 670 feet south of Highway 111) at least 320 feet long with a 90-foot transition. The applicant shall design the median opening for positive restriction of prohibited movements.

Left turn movements into Parcel Map 28422 on the east side of Dune Palms Road (approximately 617 feet south of Highway 111) with a minimum length of at least 100 feet plus a 50-foot transition. The length shall be as per Engineering Bulletin # 03-08. The applicant shall design the median opening for positive restriction of prohibited movements.

Full turn movements into the Desert Sands Unified School District Bus Facility on the east side of Dune Palms Road (approximately 1386 feet south of Highway 111) at least 200 feet long with a 90-foot reverse curve transition.

- f) Modification of the existing traffic signal at the Highway 111 and Dune Palms Road intersection as required by the abovementioned improvements and as approved by Caltrans.
- g) Establish a benchmark in the Dune Palms Road right of way and file a record of the benchmark with the County of Riverside.

ADOPTED: MARCH 22, 2005

B. TRAFFIC SIGNAL AT THE PRIMARY ENTRY ON DUNE PALMS ROAD

The applicant shall bond (the bond shall be in full force and effect for no more than five years) for installation of the traffic signal at the primary entry on Dune Palms Road when warrants are met. Applicant shall post security for 50 % of the cost to design and install the traffic signal prior to issuance of an on-site grading permit; the security shall remain in full force and effect until the signal is actually installed by the applicant or as required by the City Engineer.

The applicant shall extend improvements beyond the subdivision boundaries to ensure they safely integrate with existing improvements (e.g., grading; traffic control devices and transitions in alignment, elevation or dimensions of streets and sidewalks).

The applicant shall enter into a reimbursement agreement for their fair share of street improvements required on Highway 111 and Dune Palms Road conditioned of any parcels created by the future Parcel Map.

The applicant is responsible for construction of all improvements mentioned above. The development is eligible for reimbursement from the City's <u>Development Impact</u> <u>Fee</u> fund for some of the required improvements on Dune Palms Road in accordance with policies established for that program.

Entry drives, main interior circulation routes, corner cutbacks, bus turnouts, dedicated turn lanes and other features shown on the approved construction plans, may require additional street widths as may be determined by the City Engineer.

48. The applicant shall design street pavement sections using CalTrans' design procedure for 20-year life pavement, and the site-specific data for soil strength and anticipated traffic loading (including construction traffic). Minimum structural sections shall be as follows:

Parking Lot (Low Traffic Areas)	3.0" a.c./4.5" c.a.b.
Parking Lot (High Traffic Areas)	4.5" a.c /5.5" c.a.b.
Primary Arterial	4.5" a.c./6.0" c.a.b.

or the approved equivalents of alternate materials.

ADOPTED: MARCH 22, 2005

- 49. The applicant shall submit current mix designs (less than two years old at the time of construction) for base, asphalt concrete and Portland cement concrete. The submittal shall include test results for all specimens used in the mix design procedure. For mix designs over six months old, the submittal shall include recent (less than six months old at the time of construction) aggregate gradation test results confirming that design gradations can be achieved in current production. The applicant shall not schedule construction operations until mix designs are approved.
- 50. General access points and turning movements of traffic are limited to the following:
 - A. Primary Entry on Dune Palms Road (approximately 1130 feet south of Highway 111): Right turn in and right turn out movements are permitted. Left turn in and left turn out movements are prohibited. The applicant shall redesign the alignment of driveway #8 so its centerline projects across the street to a location that is 35 feet south of the joint property line separating parcels 3 and 4 of Parcel Map 28422.
 - B. Gas Station Entry on Dune Palms Road (approximately 670 feet south of Highway 111): Right turn in, right turn out and left turn in movements are permitted. Left turn out movement is prohibited. The applicant shall design the median opening for positive restriction of prohibited movements.
- 51. Improvements shall include appurtenances such as traffic control signs, markings and other devices, raised medians if required, street name signs and sidewalks. Midblock street lighting is not required.
- 52. Improvements shall be designed and constructed in accordance with City adopted standards, supplemental drawings and specifications, or as approved by the City Engineer. Improvement plans for streets, access gates and parking areas shall be stamped and signed by qualified engineers.

PARKING LOTS and ACCESS POINTS

- 53. The design of parking facilities shall conform to LQMC Chapter 9.150 and in particular the following:
 - A. The parking stall and aisle widths and the double hairpin stripe parking stall design.

ADOPTED: MARCH 22, 2005

- B. ADA accessibility routes between opposite Handicap Stalls shall be a minimum of 4 feet.
- C. Cross slopes should be a maximum of 2% where ADA accessibility is required including accessibility routes between buildings.
- D. Building access points shall be shown on the Precise Grading Plans to better evaluate ADA accessibility issues.

Entry drives, main interior circulation routes, corner cutbacks, bus turnouts, dedicated turn lanes, ADA accessibility route to public streets and other features shown on the approved construction plans, may require additional street widths and other improvements as may be determined by the City Engineer.

54. A raised median shall be constructed at the Gas Station Driveway off of Dune Palms Road to pass the first parking aisle.

CONSTRUCTION

55. The City will conduct final inspections of habitable buildings only when the buildings have access to publicly-maintained streets. The improvements shall include required traffic control devices, pavement markings and signage.

LANDSCAPING

- 56. The applicant shall comply with Sections 13.24.130 (Landscaping Setbacks) & 13.24.140 (Landscaping Plans), LQMC.
- 57. The applicant shall provide landscaping in the required setbacks, retention basins, common lots and parking areas.
- 58. Landscape and irrigation plans for landscaped lots and setbacks, medians, retention basins, and parks shall be signed and stamped by a licensed landscape architect.
- 59. The applicant shall submit the landscape plans for approval by the Community Development Department (CDD), prior to plan checking by the Public Works Department. When plan checking has been completed by CDD, the applicant shall obtain the signatures of CVWD and the Riverside County Agricultural Commissioner, prior to submittal for signature by the City Engineer.

ADOPTED: MARCH 22, 2005

NOTE: Plans are not approved for construction until signed by the City Engineer.

60. Landscape areas shall have permanent irrigation improvements meeting the requirements of the City Engineer. Use of lawn areas shall be minimized with no lawn, or spray irrigation, being placed within 18 inches of curbs along public streets.

QUALITY ASSURANCE

- 61. The applicant shall employ construction quality-assurance measures that meet with the approval of the City Engineer.
- 62. The applicant shall employ, or retain, qualified engineers, surveyors, and such other appropriate professionals as are required to provide the expertise with which to prepare and sign accurate record drawings, and to provide adequate construction supervision.
- 63. The applicant shall arrange for, and bear the cost of, all measurements, sampling and testing procedures not included in the City's inspection program, but which may be required by the City, as evidence that the construction materials and methods employed comply with the plans, specifications and other applicable regulations.
- 64. Upon completion of construction, the applicant shall furnish the City with reproducible record drawings of all improvement plans which were approved by the City. Each sheet shall be clearly marked "Record Drawing," "As-Built" or "As-Constructed" and shall be stamped and signed by the engineer or surveyor certifying to the accuracy and completeness of the drawings. The applicant shall have all AutoCAD or raster-image files previously submitted to the City, revised to reflect the as-built conditions.

ADUPTED: WANCH 22, 2005

MAINTENANCE

- 65. The applicant shall comply with the provisions of Section 13.24.160 (Maintenance), LQMC.
- 66. The applicant shall make provisions for the continuous and perpetual maintenance of all private on-site improvements, perimeter landscaping, access drives, and sidewalks.

FEES AND DEPOSITS

- 67. The applicant shall comply with the provisions of Section 13.24.180 (Fees and Deposits), LQMC. These fees include all deposits and fees required by the City for plan checking and construction inspection. Deposits and fee amounts shall be those in effect when the applicant makes application for plan check and permits.
 - 68. Permits issued under this approval shall be subject to the provisions of the Infrastructure Fee Program and Development Impact Fee program in effect at the time of issuance of building permit(s).

COMMUNITY DEVELOPMENT DEPARTMENT

- 69. Applicant is prohibited from placing temporary storage containers on site.
- 70. Applicant shall increase the size of the landscape planters on the north elevation (front of the building) and on the sides of the building.
- 71. Applicant shall install trees along the south property line. The trees shall be equal to or greater than the specification for the Centre at La Quinta (a two inch caliper (measured three feet from grade level after planting) and a 36 inch box or better.)
- 72. All mechanical equipment shall be screened from public view; trash and recycling containers and equipment shall be screened from public view with a block wall. Final design shall approved by the Community Development Director.
- 73. Applicant shall reduce to 35 feet in height all lighting fixtures; the design of the pole and fixture shall be consistent with existing fixtures at the Centre at La Quinta parking lot.

ADOPTED: MARCH 22, 2005

- 74. The developer shall be responsible for the construction of a bus shelter on the south side of Highway 111, west of Dune Palms Road, and shall be constructed in accordance with the City's Highway 111 Design Guidelines standard plans. The funding for the construction shall be as follows:
 - a. \$15,000 from the developer of the Centre at La Quinta (per prior condition of approval.
 - b. The City shall require the developer of the property on the southwest corner of Highway 111 and Dune Palms Road to pay the remaining 21.6% of the costs of construction.
 - c. Developer of this Site Development Permit shall be responsible for 78.4 % of the total remaining cost of construction.

The timing of the construction shall be as follows: To the extent practical, the construction is to be concurrent with the City's current project for the improvements to Highway 111 between Adams Street and Jefferson Street. To this end, the developer shall complete the construction within four months of the issuance of written Notice to Construct by the City, which notice shall not be issued earlier than January 1, 2006. If the City's Notice to Construct is issued prior to the issuance of the building permit for the commercial building, then the completion date shall be four months from the issuance of the permit. Following the issuance of this permit, the developer shall diligently work to obtain all necessary approvals for the construction, so that upon issuance of the Notice to Construct, the Developer will be in a position to proceed.

FIRE MARSHALL

75. Final conditions will be addressed when building plans are reviewed. A plan check fee must be paid to the Fire Department at the time building plans are submitted. All questions regarding Fire Marshall conditions should be directed to the Fire Department Planning & Engineering staff at (760) 863-8886.

SHERIFF DEPARTMENT

76. Final conditions will be addressed when building plans are reviewed. Prior to issuance of a building permit, applicant shall review building plans with the Sheriff's Department regarding Vehicle Code requirements, defensible space, and other law

ADOPTED: MARCH 22, 2005

enforcement and public safety concerns. All questions regarding the Sheriff's Department should be directed to the Senior Deputy at (760) 863-8950.

77. The applicant shall redesign the Parking lot/parking field by eliminating 30 parking stalls and adding more landscaping by increasing the number and size of landscape planters.